

Dual-in-line Switches

Specifications:


Contact rating:	50 V DC, 100 mA
Contact resistance:	< 50 mΩ
Insulation resistance:	> 1000 MΩ at 100 V DC
Capacity:	< 5 pF between 2 poles
Dielectric strength:	500 V, 50 Hz for the duration of 1 minute
Operating temperature:	- 20° to + 80° C
Mechanical life:	minimum 10 000 operations per pole
Shock resistance:	contact interruption < 10 μsec with triple shock in all 6 directions shock conditions: 20 G, 11 msec duration (sine half wave)
Vibration:	contact interruption < 10 μsec at vibration test in accordance with MIL-STD-202 D, method 204, condition C
Contact/Terminals:	PC terminals, phosphor bronze, Series 100: 2,0 μm gold-plated over 1 μm nickel Series 200: 0,2 μm gold-plated over 1 μm nickel
Material:	case: PBT, slide: PA
Construction:	case sealed
Slide position:	OFF
Mounting:	on pc-board
Soldering conditions:	auto-soldering – max.: 3 sec, 270° C

5

Models:

Series DSS 100

Type	Poles	Length (A)
DSS 102	2	6,6 mm
DSS 104	4	11,7 mm
DSS 106	6	16,8 mm
DSS 108	8	21,8 mm
DSS 110	10	26,9 mm



Series DSS 200

Type	Poles	Length (A)
DSS 202	2	6,6 mm
DSS 204	4	11,7 mm
DSS 206	6	16,8 mm
DSS 208	8	21,8 mm
DSS 210	10	26,9 mm

